



HD-NVR-4108VP

- 8Ch. With 1080P Realtime Live View
- H.264 / MJPEG dual codec decoding
- Max. 48 Mbps incoming bandwidth
- Support Multi-brand network cameras
- HDMI / VGA/AV simultaneous video output
- Support 1 SATA HDDs up to 6 TB, 2 USB 2.0
- Support ONVIF Standard
- Built-in Web Server, Multi-DVR Client & CMS
- 3G Dongle Support & Hi Focus DDNS Free

SPECIFICATION



Video Input	8 channel
Processor	Dual-core embedded processor
Operating System	Embedded LINUX
Hard Disk	1 SATA port, up to 6TB
Video Output	1 HDMI, 1 VGA
User Interface	GUI
Compression	H.264 / MJPEG
Video Resolution	1920×1080, 1280×1024, 1280×720, 1024×768
Video Recording	Max 48 Mbps
Video Display Split	1/4/8/9
Motion Detection	MD Zones: 396(22×18)
Video Loss	Supports
Camera Blank	Supports
Trigger Events	Recording, PTZ, Tour, Alarm, Video Push, Email, TP, Spot, Buzzer & Screen
Recording Mode	Manual, Schedule(Regular(Continuous), MD, Alarm), Stop
Search Mode	Time/Date,MD & Exact search (accurate to second)
Playback	Play, Pause, Stop, Rewind, Fast play, Slow play, Next file, Previous file, Next camera, Previous camera, Full screen, Repeat, Shuffle, Backup selection,Digital zoom
Backup Mode	USB Device / Network
Interface Ports	1 HDMI, 1 VGA, 2 USB2.0, 1 RJ45
Max User Account	20 users
Smart Phone	iPhone, iPad, Android
Protocols	HTTP, TCP/IP, IPv4/IPv6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter,PPPOE, DDNS, FTP, Alarm Server,ONVIF Version 2.0
Ethernet	RJ-45 port (10/100M)
Power Supply	DC12V/2A
Power Consumption	5W (Without HDD)-10 ~+55°C / 10~90%RH / 86~106kpa
Dimensions	215mm × 215mm × 50mm
Weight	1.25KG (without HDD)

