

HC-DQ2401N2P-LED



Product Features

- ≥ Day/night functionality
- ≥ 2MP high quality image
- ≥ Smart IR , up to 20m IR distance
- ≥ 2D/3D DNR (Digital Noise Reduction)
- ≥ BLC, HLC, DWDR
- ≥ Video Output Support BNC
- ≥ TVI/AHD/CVI/CVBS
- ≥ Supports 180° horizontal flip, 180° vertical flip
- ≥ OSD configuration menu, easy to operate
- ≥ OSD configuration menu in 11 languages
- ≥ 3-Axis
- ≥ Surge Protection 4KV
- ≥ The camera supports 24/7 full-color imaging.
- ≥ IP67 waterproof and dustproof design, high reliability



An ISO 9001:2008 Certified Company

Specifications :

CAMERA

Sensor	1/3", progressive scan, 2.0megapixel, CMOS
Lens	2.8mm
Angle of view	H: 100.9° V: 56.5° D: 121.8°
Shutter Speed	Auto/Manual, PAL: 1/25s-1/50000s NTSC: 1/30s-1/50000s
Day/Night	IR-cut filter with auto switch (ICR)
Min.Illumination	Color: 0.01Lux@F1.6,AGC ON; 0 Lux (white light on)
IR	20m IR Range(One white-light illuminator)
WDR	DWDR
Digital zoom	16x
Noise Reduction	3D DNR
Defog	Digital Defog
Flip	Supports 180° horizontal flip, 180° vertical flip
Lifetime	≥60,000 hours

VIDEO

Resolution	1080P(1920×1080), 720P(1280×720)
Frame Rate	TVI/AHD/CVI: 1080P@30fps, 1080P@25fps; 720P@30fps, 720P@25fps CVBS: PAL, NTSC
HLC	Supported
BLC	Supported
White Balance	Two modes: Auto (default), Manual



An ISO 9001:2008 Certified Company

INTERFACE

Video Output	BNC, supports TVI/AHD/CVI/CVBS
Power	5.5mm power interface

GENERAL

Power	DC 12V(±25%) Power consumption: Max 2.4 W
Temperature	-30°C to 60°C(-22°F to 140°F)
Humidity	≤95% (RH, non-condensing)
Ingress Protection	IP67
Surge Protection	4KV
Material	Plastic



An ISO 9001:2008 Certified Company