

HC-DQ5501N2P-LED



Product Features

- Day/night functionality
- Smart IR , up to 20m IR distance
- 5MP high quality image
- Supports white light illumination, 24/7 color images
- 2D DNR (Digital Noise Reduction)
- Supports 180° horizontal flip, 180° vertical flip
- OSD configuration menu, easy to operate
- OSD configuration menu in 11 languages
- 2D DNR (Digital Noise Reduction)
- Ceiling mount (default), optional backbox, wall mount bracke
- Surge protection 4KV
- IP67 waterproof and dustproof design, high reliability



An ISO 9001:2008 Certified Company

Specifications :

CAMERA

Sensor	1/2.7", progressive scan, 5.0megapixel, CMOS
Lens	2.8mm
Angle of view	H: 110.0° V: 57.0° D: 130.0°
Shutter Speed	Auto/Manual, PAL: 1/25s-1/50000s NTSC: 1/30s-1/50000s
Day/Night	IR-cut filter with auto switch (ICR)
Minimum Illumination	Color: 0.02Lux (F2.0, AGC ON) 0 lux (IR on)
IR	20m IR Range(One white-light illuminator)
WDR	DWDR
Digital zoom	16x
Noise Reduction	2D
Defog	Digital Defog
Flip	Supports 180° horizontal flip, 180° vertical flip
Lifetime	≥60,000 hours

VIDEO

Resolution	5MP@25fps: 2880(H)×1620(V); 5MP@20fps: 2592(H)×1944(V); 5MP@12.5fps:2592(H)×1944(V) 4MP: 2560(H)×1440(V) 2MP: 1920(H)×1080(V)
Frame Rate	TVI: 5MP@20fps, 5MP@12.5fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps AHD: 5MP@20fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps CVI: 5MP@25fps, 4MP@30fps, 4MP@25fps, 1080P@30fps, 1080P@25fps CVBS: PAL, NTSC
HLC	Supported
BLC	Supported
Exposure mode	4 modes: Global (default)
White balance Two modes:	Auto (default), Manual



An ISO 9001:2008 Certified Company

Day/Night

24/7 color images

Smart IR

Support

INTERFACE

Power

5.5mm power interface

Video Output

BNC, supports TVI/AHD/CVI/CVBS

GENERAL

Power

DC 12V(±25%)

Power consumption: Max 2.4 W

Working Environment

-30°C to 60°C (-22°F to 140°F)

Humidity

≤ 95% RH(non-condensing)

Dimensions

Φ118mm*96mm (diameter*height)

Material

Plastic

Surge protection

4KV

Ingress Protection

IP67



An ISO 9001:2008 Certified Company