

HC-TQ2401N2P-LED



Product Features

- ≥ Day/night functionality
- ≥ 2MP high quality image
- ≥ Smart IR , up to 20m IR distance
- ≥ 2D/3D DNR (Digital Noise Reduction)
- ≥ Video Output Support BNC
- ≥ TVI/AHD/CVI/CVBS
- ≥ Supports 180° horizontal flip, 180° vertical flip
- ≥ OSD configuration menu in 11 languages
- ≥ 3-Axis
- ≥ Surge Protection 4KV
- ≥ The camera supports 24/7 full-color imaging.
- ≥ IP67 waterproof and dustproof design, high reliability



An ISO 9001:2008 Certified Company

Specifications :

CAMERA

Sensor	1/3", progressive scan, 2.0megapixel, CMOS
Lens	4.0mm
Angle of view	H: 82.5° V: 42.1° D: 98.6°@ 4.0mm;
Shutter Speed	Auto/Manual, PAL: 1/25s-1/50000s NTSC: 1/30s-1/50000s
Day/Night	IR-cut filter with auto switch (ICR)
Min.Illumination	Color: 0.01Lux@F1.6, AGC ON; 0 Lux (white light on)
IR	20m IR Range (One white-light illuminator)
WDR	DWDR
Digital zoom	16x
Noise Reduction	3D DNR
Defog	Digital Defog
Flip	Supports 180° horizontal flip, 180° vertical flip
Lifetime	≥60,000 hours

VIDEO

Resolution	1080P: 1920(H)×1080(V) 720P: 1280(H) ×720(V)
Frame Rate	TVI/AHD/CVI: 1080P@30fps, 1080P@25fps; 720P@30fps, 720P@25fps CVBS: PAL, NTSC
HLC	Supported
BLC	Supported
Exposure mode	4 modes: Global (default)
Day/Night	24/7 Color Images
White balance	Two modes: Auto (default), Manual
Smart IR	Supports



An ISO 9001:2008 Certified Company

INTERFACE

Video Output	BNC, supports TVI/AHD/CVI/CVBS
Power	5.5mm power interface

GENERAL

Power	DC 12V(±25%) Power consumption: Max 2.88 W
Working Environment	-30°C to 60°C (-22°F to 140°F)
Humidity	≤ 95% RH(non-condensing)
Dimensions	142mm*63mm*65mm (L*W*H)
Material	Plastic
Surge protection	4KV
Ingress Protection	IP67



An ISO 9001:2008 Certified Company