

## HC-DS5500N2P-A



### Product Features

- ≥ 5MP 20fps/4MP real-time image, high resolution, true color
- ≥ AHD / TVI / CVI standard and lossless video output
- ≥ Up to 1500 TVL resolution
- ≥ CMOS progressive scan, perfectly capture the moving object
- ≥ Support OSD menu
- ≥ High speed, long distance and real time transmission
- ≥ Auto color to B / W at low illumination
- ≥ Support ICR switch, true day / night
- ≥ 20m IR night view distance
- ≥ Support COC
- ≥ Support 960H CVBS output
- ≥ Support coaxial audio transmission
- ≥ IP67



An ISO 9001:2008 Certified Company

## Specifications :

### CAMERA

Image Sensor	1 / 2.5 "CMOS
Resolution	5MP
Image Size	2560 x 1936
Video Output	AHD/TVI/CVI/CVBS
Image System	PAL/NTSC
Electronic Shutter	Auto
IR Distance	20m
Frame Rate	5MP@20fps/4MP@30fps
Min. illumination	0 lux with IR
Lens	3.6 mm
Audio	1CH Built-in Mic
Lens Mount	M12
S / N Ratio	≥52dB (AGC OFF)
Ingress Protection	IP67

### FUNCTIONS

Function Control	OSD (COC Control)
Day & Night	ICR
Digital WDR	120dB
Digital DNR	2D DNR
Global Exposure	Supported
Central Exposure	Supported
AGC	No
Auto White Balance	Supported
BLC	Supported
Front Light Compensation	No
Sharpness	Supported
Contrast	Supported
Smart IR	No



An ISO 9001:2008 Certified Company

Image Setting	Yes
Defect Correction	Auto
Language	English
Angle Adjustment	Pan: 0°~360° ; Tilt: 0°~75°; Rotation: 0°~360°

**OTHERS**

Power Supply	DC 12V (± 15%)
Power Consumption	IR Off : < 1W ; IR On : < 3W
Working Environment	-10°C ~ 40° C, 10% ~ 90% (relative humidity)
Dimensions (mm)	Φ 94.8 x 82.8
Weight	Approx. 0.2KG



An ISO 9001:2008 Certified Company