

HC-IPC-TS2200N3-SL



Product Features

- 2MP(1920x1080) H.265 coding
- Max. resolution: 1920x1080
- 24/7 full color imaging
- 30 m white light view distance
- 3D DNR, Digital WDR, HLC and BLC, Defog
- ROI coding
- DC 12V/PoE Power Supply
- Support mobile surveillance by smart phones with iOS and Android OS
- IP67 ingress protection
- Support Dual streams
- Intelligent Analytics: video blur detection, scene change detection, line crossing detection, intrusion detection



An ISO 9001:2008 Certified Company

Specifications :

CAMERA

Image Sensor	1/ 2.8" Progressive Scan CMOS Sensor
Effective Pixels	1920x1080
Electronic Shutter Speed	1s ~ 1 /100000s
Minimum Illumination	0.0126lux @F1.2, AGC ON; 0 lux with LED ON 0.0462 lux @ F2.2, AGC ON; 0 lux with LED ON
Iris Type	Fixed Iris
S/N Ratio	≥50dB
Lens	2.8mm @F1.0, horizontal field of view:97.8°/ 3.6mm @F1.0, horizontal field of view:82.5°/ 6mm @F1.0, horizontal field of view:56° (optional)*
Lens Mount	M12
IR Distance	30m
Wide Dynamic Range	Digital WDR
BLC	Yes
HLC	Yes
Defog	Yes
Digital NR	3D DNR
Angle Adjustment	Pan: 0°~360°; Tilt:0°~90°; Rotation: 0°~360°

VIDEO

Video Compression	H.265/H.264/ MJPEG
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile
Resolution	1080P(1920x1080),720P(1280x720), D1,CIF,480x240
Main Stream	60Hz:1080P(1~30fps)/720P(1~30fps) 50Hz:1080P(1~25fps)/720P(1~25fps)
Bit Rate	128 Kbps ~ 6 Mbps
Bit Rate Type	VBR/CBR
Image Settings	Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. adjustable through client software or web browser
Privacy Mask	4 areas
ROI	Supported



An ISO 9001:2008 Certified Company

INTERFACE

Network

1 RJ45 10M/100M Base TX-Ethernet

FUNCTIONS

Remote Monitoring
Online Connection

Network Protocol

Interface Protocol
Storage

Intelligent Analytics

General function

Smart Alarm
POE

Web Browsing, CMS Remote Control

Support Simultaneous monitoring for up to 3 users;

Support Multi-Stream Real time Transmission

UDP,IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP,
FTP, 802.1x, UPnP, HTTP, HTTPS, QoS Storage

ONVIF

Network remote storage; micro SD card storage

Region intrusion detection, video blur detection, scene
change detection, line crossing detection

Watermark, IP address filtering, video mask, heartbeat,
illegal login lock

Motion detection

Yes (IEEE802.3af)

ELECTRICAL

Power Supply
Power Consumption

DC12/ PoE
<4.5W

ENVIRONMENTAL

Operating Conditions

Ingress Protection

Installation

Dimensions (mm)

-20°C ~ 55°C, (-4°F ~ 131°F)

Humidity: Less than 95% noncondensing

IP67

Wall Mounting, Ceiling Mounting

62.1 × 74.8 × 73.8



An ISO 9001:2008 Certified Company