

HC-T2240N5



Product Features

- ≥ 1/2.7" 2.4Megapixel CMOS
- ≥ 25/30fps@1080P
- ≥ High speed, long distance real-time transmission
- ≥ HD and SD switchable
- ≥ Control over coaxial cable
- ≥ DWDR, Day/Night(ICR), AWB, AGC, BLC, 2D-DNR
- ≥ 6mm fixed lens (8mm optional)
- ≥ Max. IR LEDs length 50m
- ≥ IP67, DC12V



An ISO 9001:2008 Certified Company

Specifications :

Image Sensor	1/2.7" 2.4 Megapixel CMOS
Effective Pixels	1944(H) x 1080(V)
Electronic Shutter Speed	1/25~1/100000s
Minimum Illumination	0.02Lux/F2.0, 0Lux IR on
Synchronization	Internal
Video Output	1-channel BNC high definition video output/ CVBS Standard definition video output (Can switch)
Max. IR LEDs Length	50m Smart IR
Backlight Compensation	DWDR
Day/Night	Auto(ICR) / Color / B/W
Noise Reduction	3D/2D
Focal Length	3.6mm, horizontal field of view: 86.6° 6mm/8mm, horizontal field of view: 56°
Power Supply	DC12V±25%
Power Consumption	Max 4W
Working Environment	-40°C~+60°C / Less than 95%RH (no condensation)
Ingress Protection	IP67
Material	Metal (body) + Plastic (sunshield)
Dimensions	164.7mmx70mm
Weight	0.47kg

