

## HC-T2240VFN5



### Product Features

- ≥ 1/2.9" 2.4Megapixel CMOS
- ≥ 25/30fps@1080P
- ≥ High speed, long distance real-time transmission
- ≥ AHD/TVI/CVI/CVBS
- ≥ OSD Menu, Control over coaxial cable
- ≥ DWDR, Day/Night(ICR), AWB, AGC, BLC, 3DDNR
- ≥ 2.8mm~12mm Varifocal lens
- ≥ Max. IR LEDs length 50m
- ≥ IP67, DC12V



An ISO 9001:2008 Certified Company

## Specifications :

|                          |   |
|--------------------------|---|
| Image Sensor             | 1/2.9" 2.4 Megapixel CMOS   |
| Effective Pixels         | 1944(H) x 1080(V)   |
| Electronic Shutter Speed | 1/50~1/100000s  |
| Minimum Illumination     | 0.02Lux/F2.0, 0Lux IR on  |
| Synchronization          | Internal  |
| Video Output             | 1-channel BNC high definition video output/ CVBS<br>Standard definition video output (Can switch) |
| Max. IR LEDs Length      | 50m   |
| Backlight Compensation   | DWDR  |
| Day/Night                | Auto(ICR) / Color / B/W   |
| Noise Reduction          | 3D DNR  |
| OSD Menu                 | OSD (COC Control )  |
| Focal Length             | 2.8mm ~ 12mm Varifocal lens<br>horizontal field of view: 107° ~ 34.8°                             |
| Mount Type               | D14   |
| Power Supply             | DC12V±10%   |
| Power Consumption        | Max 4W  |
| Working Environment      | -40°C~+60°C / Less than 95%RH (no condensation)   |
| Ingress Protection       | IP67  |
| Material                 | Metal (body) + Plastic (sunshield)  |
| Dimensions               | 87mm×219mm  |
| Weight                   | 0.35kg  |

