

HC-IPC-DSA2200N3-SL



Product Features

- ≥ 2MP (1920x1080) H.265 coding
- ≥ Max. resolution: 1920*1080
- ≥ 24/7 full color imaging
- ≥ 30 m white light view distance
- ≥ 3D DNR, WDR, HLC and BLC, Defog
- ≥ ROI coding
- ≥ PoE Power Supply (Optional)
- ≥ Support mobile surveillance by smart phones with iOS and Android OS
- ≥ IP67 ingress protection
- ≥ Support Dual streams
- ≥ Intelligent Analytics: video blur detection, line crossing detection, intrusion detection



An ISO 9001:2008 Certified Company

Specifications :

CAMERA

Image Sensor	1/ 2.8" Progressive Scan CMOS Sensor
Effective Pixels	1920x1080
Electronic Shutter Speed	1s~ 1 /100000s
Minimum Illumination	0.012 lux @F1.2, AGC ON; 0 lux with IR
Iris Type	Fixed Iris
Lens	2.8mm @F1.0, horizontal field of view:109°/ 3.6mm @F1.0, horizontal field of view:84.8° (optional)*
Lens Mount	M12
IR Distance	30m
Wide Dynamic Range	120dB
Digital NR	3D DNR
BLC	Supported
HLC	Supported
Defog	Supported
Angle Adjustment	Pan: 0°~360°; Tilt:0°~75°; Rotation: 0°~360°

VIDEO

Video Compression	H.265/H.264/ MJPEG
H.264 Compression Standard	Baseline Profile/Main Profile/High Profile
Resolution	1080P(1920x1080),720P(1280x720), D1,CIF,480x240
Main Stream	60Hz:1080P(1~30fps)/720P(1~30fps) 50Hz:1080P(1~25fps)/720P(1~25fps)
Bit Rate	128 Kbps ~ 6Mbps
Bit Rate Type	VBR/CBR
Audio Compression	G711A / U
Image Settings	Saturation, Brightness, Chroma, Contrast, Wide Dynamic, Sharpen, NR, etc. adjustable through client software or web browser
Privacy Mask	4 areas
ROI	Supported



An ISO 9001:2008 Certified Company

INTERFACE

Network	1 RJ45 10M/100M Base-TX Ethernet
Audio	1CH built-in MIC
Video Output	No
Reset	Yes

FUNCTIONS

Remote Monitoring Online Connection	Web Browsing, CMS Remote Control Support Simultaneous monitoring for up to 3 users; Support Multi-Stream Real time Transmission
Network Protocol	UDP,IPv4,IPv6,DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, 802.1x, UPnP, HTTP, HTTPS, QoS Storage
Interface Protocol	ONVIF (Profile S,G)
Intelligent Analytics	Video blur detection, intrusion detection and line crossing Detection
Smart Alarm POE	Motion detection, SD card error, SD card full Yes, IEEE802.3af

ELECTRICAL

Power Supply	DC12/ PoE
Power Consumption	<4W

ENVIRONMENTAL

Operating Conditions	-30°C ~ 60°C, (-22°F ~ 140°F) Humidity: Less than 95% noncondensing
Ingress Protection	IP67
Dimensions (mm)	Φ 94.6 × 82.8
Installation	Ceiling mounting; (Wall mounting available with the junction box and bracket)



An ISO 9001:2008 Certified Company