

HC-TS5500N3-M



Product Features

- 5MP @20fps/4MP Real-time Image, High Resolution, True Color
- AHD/TVI/CVI Standard and Lossless Video Output
- Up to 1500 TVL Resolution
- CMOS Progressive Scan, Perfectly Capture the Moving Object
- Support OSD Menu
- High Speed, Long Distance and Real time Transmission
- Auto Color to B/W at Low illumination
- Support ICR Switch, True Day/night
- 30m IR night View Distance
- Support COC



An ISO 9001:2008 Certified Company

Specifications :

CAMERA

Image Sensor	1/ 2.5"CMOS
Resolution	5MP
Image Size	2560x1936
Video Output	AHD/TVI/CVI/CVBS
Image System	PAL/NTSC
Electronic Shutter	Auto
IR Distance	30m
Frame rate	5MP@20fps/4MP@30fps
Min. illumination	Color: 0.01lux@F1.2, AGC ON; B/W: 0 lux with IR
Lens Mount	M12
Lens	3.6mm, horizontal field of view: 86.6° 6mm, horizontal field of view: 56°
S/N Ratio	≥52dB (AGC OFF)

FUNCTIONS

Function Control	OSD (COC Control)
Day & Night	ICR
Digital WDR	Yes
Digital NR	Yes
Global Exposure	Yes
Central Exposure	No
AGC	Yes
Auto White Balance	Yes
BLC	Yes
Front Light Compensation	No
Contrast	Yes
Sharpness	Yes
Smart IR	No



An ISO 9001:2008 Certified Company

Image Settings	Yes
Defect Correction	Auto
Language	English
Angle Adjustment	Pan: 0°~360°: Tilt 0°~80°: Rotation:0°~360°

OTHERS

Power Supply	DC 12V(± 10%)
Power Consumption	IR Off : < 1W: IR On :< 3.5W
Working Environment	-30°C~50° C, 10%~90% (relative humidity)
Dimensions (mm)	167.5 x 74. 5 x 74. 5
Weight (net)	Approx. 0.37KG
Ingress Protection	IP67



An ISO 9001:2008 Certified Company