

HC-T1300N2



Product Features

- ≥ Max 30fps@960P
- ≥ HD and SD output switchable
- ≥ 3.6mm fixed lens (6mm optional)
- ≥ Max.IR Length 20m, Smart IR
- ≥ IP67, DC12V



An ISO 9001:2008 Certified Company

Specifications :

CAMERA

Image Sensor	1/3" CMOS
Effective Pixels	1280(H) × 960(V), 1.3MP
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25~1/100000s
Minimum Illumination	0.05Lux/F2.0, 0Lux IR on
S/N Ratio	More than 65dB
IR Distance	Up to 20m (66feet)
IR On/Off Control	Auto / Manual

LENS

Lens Type	Fixed lens / Fixed iris
Mount Type	Board-in
Focal Length	3.6mm, horizontal field of view: 72.3° 6mm, horizontal field of view: 56°
Max Aperture	F2.0
Close Focus Distance	500mm (400mm/1300mm) 19.69" (15.75"/51.18")

VIDEO

Resolution	960P (1280×960)
Frame Rate	25/30fps@960P
Video Output	1-channel BNC high definition video output / CVBS video output (Can switch)
Day/Night	Auto (ICR) / Manual
OSD Menu	Multi-language
BLC Mode	BLC / HLC / DWDR
WDR	DWDR
Gain Control	AGC
Noise Reduction	2D
White Balance	Auto / Manual
Smart IR	Auto / Manual



An ISO 9001:2008 Certified Company

ELECTRICAL

Power Supply	12V DC±25%
Power Consumption	Max 2.8W (12V DC, IR on)

ENVIRONMENTAL

Operating Conditions	-40°C~+60°C (-40°F~+140°F)/ Lessthan90%RH
Storage Conditions	-40°C~+60°C (-40°F~+140°F)/ Lessthan90%RH

CONSTRUCTION

Casing	Plastic + metal
Dimensions	154.3mm×69.8mm×69.8mm (6.07"×2.75"×2.75")
Net Weight	0.20kg (0.44lb)
Gross Weight	0.27kg (0.60lb)



An ISO 9001:2008 Certified Company