

HC-D2200N3



Product Features

- ≥ Max 30fps@1080P
- ≥ HD and SD output switchable
- ≥ 3.6mm fixed lens
- ≥ Max.IR Length 30m, Smart IR
- ≥ DC12V



An ISO 9001:2008 Certified Company

Specifications :

CAMERA

Image Sensor	1/2.7" CMOS
Effective Pixels	1920(H) × 1080(V), 2MP
Scanning System	Progressive
Electronic Shutter Speed	PAL: 1/25~1/100000s NTSC: 1/30~1/100000s
Minimum Illumination	0.02Lux/F2.0, 0Lux IR on
S/N Ratio	More than 65dB
IR Distance	Up to 30m (98feet)
IR On/Off Control	Auto / Manual

LENS

Lens Type	Fixed lens / Fixed iris
Mount Type	Board-in
Focal Length	2.8mm, horizontal field of view: 107° 3.6mm, horizontal field of view: 89.9°
Max Aperture	F2.0
Close Focus Distance	600mm (1800mm) 23.62"(70.87)

VIDEO

Resolution	1080P (1920×1080)
Frame Rate	25/30fps@1080P, 25/30/50/60fps@720P
Video Output	1-channel BNC high definition video output / CVBS video output (Can switch)
Day/Night	Auto (ICR) / Manual
OSD Menu	Multi-language
BLC Mode	BLC / HLC / DWDR
WDR	DWDR
Gain Control	AGC
Noise Reduction	2D
White Balance	Auto / Manual
Smart IR	Auto / Manual



An ISO 9001:2008 Certified Company

ELECTRICAL

Power Supply	12V DC±25%
Power Consumption	Max 2.8W (12V DC, IR on)

ENVIRONMENTAL

Operating Conditions	-40°C~+60°C (-40°F~+140°F)/ Lessthan90%RH
Storage Conditions	-40°C~+60°C (-40°F~+140°F)/ Lessthan90%RH

CONSTRUCTION

Casing	Plastic
Dimensions	Φ85.4mm × 69.1mm (Φ3.36"×2.72")
Net Weight	0.11kg (0.24lb)
Gross Weight	0.17kg (0.37lb)



An ISO 9001:2008 Certified Company