

2MP 25X NETWORK PTZ DOME CAMERA

HC-IPC-SDQ42520L



Product Features

- ≥ High quality image with 2MP, 1/2.8" CMOS sensor
- ≥ 1920x1080@30fps in the main stream
- ≥ Smart H.265, H.265, H.264, MJPEG
- ≥ 25X Optical Zoom
- ≥ Smart IR, up to 100m (328ft) IR distance
- ≥ DC 12V±25% or PoE+ (IEEE 802.3at)
- ≥ Alarm 2CH in and 1CH out, Audio 1CH in and 1CH out
- ≥ IP67 Ingress Protection
- ≥ IK10 Vandal Resistant




An ISO 9001:2008 Certified Company



2MP 25X NETWORK PTZ DOME CAMERA

HC-IPC-SDQ42520L



UPTO
25X
OPTICAL
ZOOM



MicroSD Card Support

Use a MicroSD Card to record your video; it can support up to 256GB of data.

Specifications:

Camera

Sensor	1/2.8", 2.0 megapixel, progressive scan, CMOS
Min. Illumination	Colour: 0.001 Lux (F1.5, AGC ON) 0 Lux with IR
Day/Night	IR-cut filter with auto switch (ICR)
Shutter	Auto/Manual, 1 ~ 1/100000s
WDR	120dB
S/N	>52dB

Lens

Lens type	5 ~ 125mm, AF automatic focusing and motorized zoom lens
Digital Zoom	16
Optical Zoom	25
Iris	Auto; F1.5 ~ F4.0
Field of View (H)	54.37° ~ 2.68°
Field of View (V)	32.23° ~ 1.51°
Field of View (D)	66.88° ~ 3.16°
IR Range	Up to 100m (328 ft) IR range
Wavelength	850nm
IR On/Off Control	Auto/Manual

Video

Video Compression	Smart H.265, H.265, H.264, MJPEG
Frame Rate	Main Stream: 2MP (1920x1080), Max 60fps; Sub Stream: 2MP (1920x1080), Max 60fps; Third Stream: D1 (720x576), Max 60fps;
Video Bit Rate	128 Kbps~16 Mbps
U-code	Support
ROI	Support
Video Stream	Triple streams
OSD	Up to 8 OSDs
Privacy Mask	24 areas, up to 4 areas per scene



Image

White Balance	Auto/Outdoor/Fine Tune/Sodium Lamp/Locked/Auto2
Digital Noise Reduction	2D/3D DNR
Smart IR	Support
Flip	Normal/Flip Vertical/Flip Horizontal/180°
HLC	Support
BLC	Support
Defog	Digital Defog

Events

Basic Detection	Motion detection, Audio detection, Tampering Alarm
Auto Tracking	Support
General Function	Watermark, IP Address Filtering, Alarm input, Alarm output, Access Policy, ARP Protection, RTSP Authentication, User Authentication

Audio

Audio Compression	G.711U,G.711A
Audio Bitrate	64 Kbps
Two-way Audio	Support
Suppression	Support
Sampling Rate	8 kHz

Storage

Edge Storage	Micro SD, up to 256 GB
Network Storage	ANR, NAS(NFS)

Network

Protocols	IPv4, IGMP, ICMP, ARP, TCP, UDP, DHCP, PPPoE, RTP, RTSP, RTCP, DNS, DDNS, NTP, FTP, UPnP, HTTP, HTTPS, SMTP, 802.1x, SNMP, QoS, RTMP, SSL/TLS
Compatible Integration	ONVIF (Profile S, Profile G, Profile T), API, SDK
User/Host	Up to 32 users. 3 user levels: administrator, operator and common user



Pan & Tilt

Pan Range	360° (endless)
Pan Speed	0.1°/s ~ 200°/s Preset speed: 240°/s
Tilt Range	-15° ~ 90° (auto reverse)
Tilt Speed	0.1°/s ~ 80°/s Preset speed: 200°/s
Number of Presets	1024
Preset Patrol	16 patrols, up to 64 presets for each patrol
Route Patrol	16 patrols, up to 32 actions for each patrol
Recorded Patrol	16 patrols, up to 128 actions for each patrol
Patrol Stay Time	15s ~ 1800s
Preset Image Freeze	Support
Home Position	Support

Interface

Audio I/O	1/1
Alarm I/O	2/1
Serial Port	1 RS485
Network	1 RJ45 10M/100M Base-TX Ethernet
Video Output	1 BNC

General

Power	DC12V(±25%, 3A), PoE+(IEEE 802.3at) Power consumption: MAX 21W
Dimensions (Ø x H)	Ø166 x 295mm (Ø6.5" x 11.6")
Weight	3.05kg(6.72lb)
Working Environment	-40° ~ 70° (-40°F ~ 158°F)°Humidity: ≤95% RH (non-condensing)
Surge Protection	6KV
Reset Button	Support
Ingress Protection	IP67 & IK10

