

HC-T2401N3P-A



Product Features

- ≥ 2.4MP Image Resolution, True Color
- ≥ 1920×1080 real-time image, high resolution, true color
- ≥ AHD / TVI / CVI lossless HD video output
- ≥ Support 960H CVBS output
- ≥ CMOS progressive scan, perfectly capturing the moving object Support OSD menu
- ≥ High speed, long distance and real time transmission
- ≥ Support noise reduction function
- ≥ IP67
- ≥ Support coaxial audio transmission
- ≥ Support COC



An ISO 9001:2008 Certified Company

Specifications :

CAMERA

Image Sensor	1/ 2.8" CMOS
Resolution	2.4MP
Image Size	1920x1080
Video Output	AHD/TVI/CVI/CVBS
Audio	1CH built-in MIC
Image System	PAL/NTSC
Electronic Shutter	Auto
IR Distance	30m
Frame Rate	30fps (60Hz); 25fps (50Hz)
Min. illumination	0 lux (LED ON)
Lens	3.6mm, horizontal field of view: 97°
Lens Mount	M12
S / N Ratio	≥52dB (AGC OFF)
Ingress Protection	IP66

FUNCTIONS

Function Control	OSD (COC Control)
ICR	No
Digital WDR	Yes
Digital DNR	Yes, 2D DNR
AGC	Yes
Auto White Balance	Yes
Defog	No
BLC	Yes
Front Light Compensation	No
HLC	Yes
Sharpness	Yes
Contrast	Yes



An ISO 9001:2008 Certified Company

Image Setting	Yes
Defect Correction	Auto

OTHERS

Power Supply	DC 12V (± 15%)
Power Consumption	< 1W ;
Working Environment	-30°C ~ 50° C, 10% ~ 90% (relative humidity)
Dimensions (mm)	162.1× 74.8× 73.8
Weight (net)	Approx. 0.37KG



An ISO 9001:2008 Certified Company