

## HD-NVR-4328H8-4K



### Product Features

- ≥ 32CH Support 12MP/ 8MP / 6MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P/960H/D1/CIF IP Video input
- ≥ Adopt standard H.265+, H.265 and H.264 high profile compression format to get high-quality video at much lower bit rate
- ≥ Playback :16 CH simultaneous playback
- ≥ DHCP, DDNS, PPoE network protocol and CMS supported
- ≥ Remote control via web or CMS : preview, playback, backup, PTZ and configuration
- ≥ 4K Output True High Resolution Display
- ≥ Multi-mode recording: manual / timer / motion / sensor/POS/AI recording
- ≥ Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device,
- ≥ Multi- user online simultaneously
- ≥ Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- ≥ Powerful smart phone & Pad surveillance with iOS and Andriod OS



An ISO 9001:2008 Certified Company

## Specifications :

### SYSTEM

Compression	H.265+/H.265/H.264 Standard
OS	Embedded Linux

### VIDEO

Network Access Bandwidth	256 Mbps Incoming/ 256 Mbps Outgoing
Input Resolution	12MP,8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 960P, 720P,960H, D1, CIF
Network Access	32 CH IPC Input
Output	HDMI×1: 3840×2160 @60fps/3840×2160@30fps/ /1920×1080/1280×1024/1024×768 VGA×1:1920×1080/1280×1024/1024×768

### AUDIO

Input	32 CH IPC audio input
2-way Audio	RCA ×1
Local Output	RCA ×1
Audio Compression	G.711(U/A)

### RECORD

Resolution	12MP@20fps;8MP/6MP/5MP,4MP, 3MP/1080P/1280X1024/960P/720P/ 960H/D1/CIF
Frame Rate	25fps/30fps (PAL/NTSC)
Record Stream	Dual Stream recording

### PLAYBACK

Simultaneous Playback Function	Max 16 CH Play, Pause, FF, FB, digital zoom, etc
-----------------------------------	---

### NETWORK

Network Protocol	TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP, HTTP, HTTPs, 802.1X, ONVIF,etc.
------------------	---



An ISO 9001:2008 Certified Company

### **FACE INTERFACE**

Channel  
Face Picture Database  
Database Management  
Face Picture

32CH  
32 libraries 5000 Face Picture  
Add, modify, delete and search face picture  
Supports allow list and block list alarm

### **STORAGE**

HDD  
Max Capacity for 1 Single HDD

SATA×8  
8T per HDD: E - SATA × 1

### **BACKUP**

Local Backup  
Network Backup

U disk, USB mobile HDD  
Yes

### **INTERFACE**

Alarm In  
Alarm Output  
RJ 45  
RS 485

16CH  
4CH  
RJ45 10/100/1000 Mbps × 1  
Yes (Full-duplex) ; Connectors For PTZ or keyboard

USB  
Remote Controller  
PoE Port  
PoE Standard  
PoE Output Power

USB 2.0 × 1 , USB 3.0 × 1  
Optional  
RJ45 X 16  
IEEE802.3af  
≤ 150W

### **ELECTRICAL**

Power Supply  
Consumption

ATX 300W  
≤15W(without HDD and PoE power supply)

### **ENVIRONMENTAL**

Working Environment  
Dimensions(mm)

-10~50 °C, 10%~ 90% humidity  
445 × 436 × 90 ( W × D × H )

