

HD-NVR-5208S



Product Features :

- Support Smart H.265/H.265/H.264 video formats
- 32-channel input
- Supports mainstream cameras of ONVIF conformance(Profile S, Profile G, Profile T) and RTSP protocols
- Support 2-ch HDMI, 1-ch VGA. HDMI1 and HDMI2 up to 4K (3840x2160) resolution
- HDMI1, HDMI2, VGA independent outputs provided
- Up to 12 Megapixels resolution recording
- Support RAID 0, 1, 5, 6, 10
- 8 SATA HDDs, Up to 12TB for each HDD
- Various fisheye dewarping modes for live view and playback for both web interface and GUI
- Support N+1 Hot spare



An ISO 9001:2008 Certified Company

Specifications :

VIDEO AND AUDIO INPUT

IP Video Input	32 Channel
Two-Way Audio Input	1-Channel,RCA

NETWORK

Incoming Bandwidth	384Mbps
Outgoing Bandwidth	384Mbps
Remote Users	128
Protocols	TCP/IP, P2P, UPnP, NTP, DHCP, PPPoE, HTTP, HTTPS, DNS, DDNS, SNMP, SMTP, NFS

VIDEO AND AUDIO OUTPUT

HDMI/VGA Output	VGA: 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz HDMI1/HDMI2(HDMI audio output is not supported): 4K (3840x2160)/30Hz, 1920x1080p/60Hz, 1920x1080p/50Hz, 1600x1200/60Hz, 1280x1024/60Hz, 1280x720/60Hz, 1024x768/60Hz
-----------------	--



An ISO 9001:2008 Certified Company

DECODING

Compression	Smart H.265/H.265/H.264
Live View/ Playback	12MP/8MP/6MP/5MP/4MP/3MP/1080p/960p/720P/ D1/2CIF/CIF
Capability	2 x 12MP@30, 4 x 4K@30, 8 x 4MP@30, 9 x 4MP@25, 16 x 1080P@30

HARD DISK

SATA	8 SATA interfaces
Capacity	up to 12TB for each HDDs
eSATA	1 eSATA interface

SMART

VCA Detection	Intrusion Detection, Cross Line Detection, Enter Area, Leave Area, Defocus Detection, Scene Change Detection, Auto Tracking, Object Left Behind, Object Removed, Vehicle Control, Temperature Detection (Fire Detection, Smoking Detection, Temperature Measurement, Smoke and Fire Detection), Ultra Motion Detection (UMD), Video Metadata, Traffic Monitoring Motor Vehicle Search, Non-Motor Vehicle Search, Human Body Search, General Search, People Counting Report
---------------	---

VCA Search



An ISO 9001:2008 Certified Company

EXTERNAL INTERFACE

Network Interface	2 RJ45 10M/100M/1000M self-adaptive Ethernet Interfaces
Serial Interface	1 x RS232, 1 x RS485
USB Interface	Front panel: 2 x USB2.0,Rear panel: 1 x USB3.0
Alarm in	16 channel
Alarm out	4 channel

GENERAL

Power Supply	100 ~ 240 VAC Power Consumption: ≤ 25 W(without HDD)
Working Environment	-10°C ~ + 55°C (+14°F ~ +131°F), Humidity ≤ 90% RH(non-condensing)
Dimensions	442mm ×425mm× 89mm (17.4" × 16.8" ×3.5")
Weight (without HDD)	≤ 5.7Kg (12.57 lb)



An ISO 9001:2008 Certified Company