

HF-SPE03



Product Features

- ≥ 2 ports PoE
- ≥ 1 port Uplink
- ≥ AI Watchdog Function
- ≥ 6KV Lightning & 8KV ESD Protection
- ≥ Support bt 60W High Power
- ≥ Compact Design, Competitive Solution



An ISO 9001:2008 Certified Company

Specifications :

Ports

- ≥ PoE (1):10/100Mbps PoE port (RJ45)
- ≥ PoE (2):10/100Mbps PoE port (RJ45),
- ≥ Support bt 60W High Power LAN:10/100Mbps uplink port (RJ45)

Transmission Rate

- ≥ 200Mbps Full Duplex; 10 or 100Mbps Half Duplex

Transmission Distance

- ≥ 130m(Max Cascade 5 Times)

Performance Specification

- ≥ Bandwidth:0.6Gbps
- ≥ Network Latency (10 to 100Mbps):
16μs (use the 64byte package size)
- ≥ MAC address table: 2K
- ≥ The Frame Filter & Transmission Rate: 14800pps
the most for 10M port, 148800pps the most for 100M port



An ISO 9001:2008 Certified Company

Networking Standard

- ≥ IEEE 802.3i 10BASE-T
- ≥ IEEE 802.3u 100BASE-TX,
- ≥ IEEE 802.3x Flow Control
- ≥ IEEE 802.3af/at/bt Power over Ethernet

Power Support

Power Input: PoE Powered by Total ≤ 60W

AI Watchdog: Port 1~2

Power Output: PoE 1 Port: 1/2(+52V), 3/6(GND) ≤ 30W

PoE 2 Port: 1245(+53V), 3678(GND)

Compatible 1/2(+52V), 3/6(GND) ≤ 60W

Protection Level

- ≥ Lightning Protection: 6KV, Per: IEC61000-4-5
- ≥ ESD Protection: 8KV, Per: IEC61000-4-2



An ISO 9001:2008 Certified Company

Physical Specifications

- ≥ Size(L*W*H): 102mm*34mm*20.5mm, Weight: 0.045KG
Indoor 156mm*92mm*42mm, Weight: 0.1KG Outdoor

Working Environment

- ≥ Operating Temperature: -30°~60°
- ≥ Storage Temperature: -40°~70°
- ≥ Operating Humidity: 10%~90% Non-condensing
- ≥ Storage Humidity: 5%~90% Non-condensing

Warranty

- ≥ 1 year



An ISO 9001:2008 Certified Company