

## HD-NVR-4216T



### Product Features

- Support 16CH 8MP/6MP/5MP/4MP/3MP/1080P/1280×1024/960P/720P/960H/DI/CIF IP video input
- Adopt standard H.265 and H.264 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphic User Interface ( GUI ), Windows style operation by mouse
- Search : time slice, time, event, tag and smart search
- Support multiple VCA (Video Content Analytics) events, such as object abandoned/missing, region intrusion, tripwire, video tampering, etc.
- Support POS information overlay on live view and playback Playback : 16CH simultaneous playback
- Express and flexible backup via USB, network and so on Pentaplex : preview, record, playback, backup and remote access DHCP, DDNS, PPPoE network protocol
- Remote control via Web or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device Multi-user online simultaneously
- Authorization management, log view and device status view 4K ultra high resolution output, true high resolution display Support NAT function and QRCode scanning by mobile phones
- Powerful mobile surveillance by smart phones with iOS and Andriod OS



An ISO 9001:2008 Certified Company

## Specifications :

### SYSTEM

OS	Embedded Linux
Network Access	16 CH IPC input

### VIDEO

Incoming Bandwidth	112 Mbps
Outgoing Bandwidth	112 Mbps
Compression	H.265S / H.265+ /H.265 /H.264
Input Resolution	8MP/6MP/ 5MP/4MP/3MP/1080P/1280x1024/960P/ 720P/960H/D1/CIF
Output	HDMIx1: 3840x2160 /1920x1080 /1280x1024 / 1024x768 VGA: 1920x1080/ 1280x1024/ 1024x768 HDMI and VGA output the same video source
Multi-screen display	1/4/6/8/9/13/16

### AUDIO

Input	16 CH IPC audio input
2-way Audio	RCA x1
Local Output	RCA x1
Compression	G.711(U/A)

### RECORD

Resolution	8MP/6MP/5MP/4MP/3MP/1080P/1280x1024/ 960P/720P/960H/D1/CIF
Frame Rate	25fps/30fps (PAL/NTSC)
Bit Stream	32Kbps-10Mbps
Image Quality	5 Level

### PLAYBACK

Simultaneous Playback	Max 16 CH
-----------------------	-----------

### NETWORK

Interface	RJ45 10/100/1000 Mbps x 1
Network Protocol	TCP / IP, IPv4, IPv6, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP, HTTP, HTTPS, 802.1x, RTSP, SNMP, ONVIF, etc.



An ISO 9001:2008 Certified Company

### STORAGE

HDD SATA×2  
Max Capacity for 1 Single HDD 8T

### BACK UP

USB Backup Yes

### INTERFACE

Alarm In 4  
Alarm Output 1  
Communication RS485, connect to PTZ and keyboard  
Remote Optional  
USB USB2.0×2

### ELECTRICAL

Power Supply DC 12V/3A  
Consumption ≤15W(without HDD)

### ENVIRONMENTAL

Working Environment -10~50 °C, 10%~ 90% humidity  
Dimensions(mm) 380×268×45 (W × D × H )



An ISO 9001:2008 Certified Company