

## HF-SGGFH24-420W



### Product Features

- ≥ 24\*10/100/1000Base-T RJ45 ports support PoE power supply
- ≥ 2 Gigabit uplink SFP ports, supporting optical fiber connection to meet the needs of long-distance wiring and aggregation networking
- ≥ Standard exchange mode: All ports communicate freely, suitable for ordinary data transmission environment
- ≥ AI PoE: Automatically detect the power receiving port, find a dead device, and restart the device after power off
- ≥ AI QoS: Prioritize the identified video data to make video transmission smoother.



An ISO 9001:2008 Certified Company

## Specifications:

Network standard	IEEE 802.3i, IEEE 802.3u, IEEE 802.3x IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at
Port	24 10/100/1000Mbps RJ45 port 2 Gigabit SFP port
PoE	24 10/100/1000Mbps RJ45 PoE ports Total Power Budget 250W Single port max 30W
LEDs	26 Link/Act LEDs 24 POE LEDs 1 Power LEDs
Performance	Forwarding mode: Storage Forwarding Bankplane Bandwidth : 52Gbps Packet forwarding rate: 38.7Mpps Support 8K MAC address table
Input power	100-240V/50-60Hz
Dimension(L×W×H)	440mm×180mm×44mm



An ISO 9001:2008 Certified Company