

HD-NVR-5110L



Product Features :

- ≥ Support H.265+(Smart Encode)/H.265/H.264 Video formats
- ≥ 10-channel input
- ≥ Third-party IP cameras supported with ONVIF conformance Profile S, Profile G, Profile C, Profile Q, Profile A, Profile T
- ≥ Support 1-ch HDMI, 1-ch VGA, HDMI at up to 1920 x 1080P resolution
- ≥ Up to 5 Megapixels resolution recording
- ≥ HDMI and VGA simultaneous output
- ≥ 1 SATA HDD up to 6 TB for each HDD
- ≥ ANR technology to enhance the storage reliability when the network is disconnected



An ISO 9001:2008 Certified Company

Specifications:

VIDEO AND AUDIO INPUT

IP Video Input 10-Channel

NETWORK

Incoming Bandwidth 30Mbps
Outgoing Bandwidth 30Mbps
Remote Users 128
Protocols IPv4, IPv6, RTSP, UDP, SMTP, NTP, DDNS, DNS, HTTP, HTTPS, FTP, P2P, UPnP, NTP, DHCP, PPPoE, SnMP, ONVIF

VIDEO AND AUDIO OUTPUT

HDMI/VGA Output
Recording Resolution

HDMI:
1920x1080p /60Hz,
1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz
VGA:
1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz
5MP/4MP/3MP/1080p/960p/720p/D1/
2CIF/CIF

DECODING

Compression H.265+(Smart Encode), H.265, H.264
Live view/ Playback 5MP/4MP/3MP/1080p/960p/720P/
D1/2CIF/CIF



An ISO 9001:2008 Certified Company

HARD DISK

SATA
Capacity

1 SATA interfaces
up to 6TB for each Disk

EXTERNAL INTERFACE

Network Interface
USB Interface

1 RJ-45 10M/100M self-adaptive Ethernet Interface
Rear panel : 2 x USB2.0

GENERAL

Power Supply
Consumption (without HDD)
Working Temperature
Working Humidity
Dimensions
Weight (without HDD)

12V DC
≤ 5 W
-10°C ~ + 55°C (+14°F ~ +131°F)
Humidity ≤ 90% RH(non-condensing)
260.0mm × 240.2mm ×43.6mm (10.2"× 9.5"×1.7")
≤ 1 Kg (2.2 lb)



An ISO 9001:2008 Certified Company