

HD-NVR-4232T



Product Features

- 32 CH Support 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P IP input
- Adopt standard H.265 and H.264 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphic User Interface (GUI), Windows style operation by mouse,4K Output True High Resolution Display
- Multi-mode recording: manual / timer / motion / sensor
- Playback :16 CH simultaneous playback
- Search : time slice, time, event (manual, sensor, motion), tag search
- Express and flexible backup via USB, network and so on
- Pentaplex : preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device,Multi-user online simultaneously
- Authorization management, log view and device status view,4K output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with iOS and Andriod OS



An ISO 9001:2008 Certified Company

Specifications :

SYSTEM

OS	Embedded Linux
Main Processing Chip	ARM Cortex A17

VIDEO

Incoming Bandwidth	112 Mbps
Outgoing Bandwidth	112 Mbps
Video Compression	Smart H.265, H.265, H.264
Input Resolution	8MP, 5MP, 4MP, 3MP, 1080P, 960P, 720P Real Time
Network Access	32 CH IPC Input
Output	HDMI×1: 3840×2160/1920×1080/1280×1024 1024×768 VGA×1:1920×1080/1280×1024/1024×768

AUDIO

Input	32 CH IPC audio input
2-way Audio	RCA ×1
Local Output	RCA ×1

RECORD

Resolution	8MP, 5MP, 4MP, 3MP, 1080P, 960P, 720P
Frame Rate	25fps/30fps (PAL/NTSC)
Bit Stream	32Kbps-10Mbps
Image Quality	5 Level

PLAYBACK

Simultaneous Playback	Max 16 CH
-----------------------	-----------

NETWORK

Interface	RJ45 10/100/1000 Mbps × 1
Network Protocol	IPv4, IPv6, RTSP, UDP, SMTP, NTP, DDNS, DNS, HTTP, HTTPS, FTP, P2P, UPnP, NTP, DHCP, PPPoE, SnMP, ONVIF



An ISO 9001:2008 Certified Company

STORAGE

HDD SATA×2
Max Capacity for 1 Single HDD 8T

BACK UP

USB Backup Yes

INTERFACE

Alarm In 4
Alarm Output 1
Communication RS485 (full-duplex), connect to PTZ and keyboard
Remote Optional
USB USB2.0×2(one in the front panel and the other in the rear panel)

ELECTRICAL

Power Supply DC 12V/3A
Consumption ≤15W(without HDD)

ENVIRONMENTAL

Working Environment -10~50 °C, 10%~ 90% humidity
Dimensions(mm) 380×268×52 (W × D × H)
Case 1.5U



An ISO 9001:2008 Certified Company