

HD-NVR-5232L



Product Features :

- ≥ Support H.265(Smart Encode)/H.265/H.264 Video formats
- ≥ 32-channel input
- ≥ Third-party IP cameras supported with ONVIF conformance Profile S, Profile G, Profile C, Profile Q, Profile A, Profile T
- ≥ Support 1-ch HDMI, 1-ch VGA, HDMI at up to 4K(3840x2160) resolution
- ≥ Up to 8 Megapixels resolution recording
- ≥ HDMI and VGA simultaneous output
- ≥ 2 SATA HDD up to 6 TB for each HDD
- ≥ ANR technology to enhance the storage reliability when the network is disconnected



An ISO 9001:2008 Certified Company

Specifications:

VIDEO AND AUDIO INPUT

IP Video Input 32-Channel

Two-way Audio Input 1-Ch, RCA

NETWORK

Incoming Bandwidth 64Mbps

Outgoing Bandwidth 64Mbps

Remote Users 128

Protocols IPv4, IPv6, RTSP, UDP, SMTP, NTP, DDNS, DNS, HTTP, HTTPS, FTP, P2P, UPnP, NTP, DHCP, PPPoE, SnMP, ONVIF

VIDEO AND AUDIO OUTPUT

HDMI/VGA Output

HDMI:
4K (3840x2160) /30Hz, 1920x1080p /60Hz,
1920x1080p /50Hz, 1600x1200 /60Hz, 1280x1024
/60Hz, 1280x720 /60Hz, 1024x768 /60Hz

VGA:
1920x1080p /60Hz, 1920x1080p /50Hz, 1600x1200 /60Hz,
1280x1024 /60Hz, 1280x720 /60Hz, 1024x768 /60Hz

Recording Resolution 8MP/6MP/5MP/4MP/3MP/1080p/960p/720p/D1/
2CIF/CIF

Audio Output 1-Ch, RCA

Synchronous Playback 16-Channel



An ISO 9001:2008 Certified Company

DECODING

Compression	H.265+(Smart Encode), H.265, H.264
Live view/ Playback	8MP/6MP/5MP/4MP/3MP/1080p/960p/720P/ D1/2CIF/CIF
Capability	1 x 4K@30, 2 x 4MP@30, 4 x 1080p@30, 8 x 720p@30

HARD DISK

SATA	2 SATA interfaces
Capacity	up to 6TB for each Disk

EXTERNAL INTERFACE

Network Interface	1 RJ-45 10M/100M/1000M self-adaptive Ethernet Interface
USB Interface	Rear panel : 2 x USB2.0

GENERAL

Power Supply	12V DC
Consumption (without HDD)	≤ 5 W
Working Temperature	-10°C ~ + 55°C (+14°F ~ +131°F)
Working Humidity	Humidity ≤ 90% RH(non-condensing)
Dimensions	260.0mm × 240.2mm ×43.6mm (10.2"× 9.5"×1.7")
Weight (without HDD)	≤ 1 Kg (2.2 lb)



An ISO 9001:2008 Certified Company