

## HD-NVR-5432T



### Product Features

- 32 CH Support 12MP / 8MP / 5MP / 4MP / 3MP / 1080P / 960P / 720P IP input
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphic User Interface ( GUI ), Windows style operation by mouse,4K Output True High Resolution Display
- Multi-mode recording: manual / timer / motion / sensor
- Playback :16 CH simultaneous playback
- Search : time slice, time, event ( manual, sensor, motion ), tag search
- Express and flexible backup via USB, network and so on
- Pentaplex : preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device,Multi-user online simultaneously
- Authorization management, log view and device status view,4K output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- Support NAT function and QRCode scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with iOS and Andriod OS



An ISO 9001:2008 Certified Company

## Specifications :

### SYSTEM

Compression H.264 and H.265 Standard  
OS Embedded Linux

### VIDEO

Network Input 32 CH IPC Input  
Video Compression Smart H.265, H.265, H.264  
Incoming Bandwidth 256Mbps  
Outgoing Bandwidth 256Mbps  
Input Resolution 12MP, 8MP, 5MP, 4MP, 3MP, 1080P, 960P, 720@25/30fps  
Output HDMI×1:4K×2K/1920×1080/1280×1024  
VGA×1:1920×1080/1280×1024

### AUDIO

Input 32 CH IPC audio input  
2-way Audio RCA ×1  
Local Output RCA ×1

### RECORD

Resolution 12MP, 8MP, 5MP, 4MP, 3MP, 1080P, 960P, 720P  
Record Stream Dual Stream Recording  
Mode Manual, Timer, Motion, Sensor

### PLAYBACK

Simultaneous Playback Max 16 CH  
Search Time Slice/Time/Event/Tag Search  
Smart Search Highlighted Color to Display the Camera record in a Certain Period of Time, Different Color refer to Different Record Events  
Function Play, Pause, FF, FB, Digital Zoom, etc

### ALARM

Mode Manual, Sensor, Motion, Exception  
Input 8 CH Local alarm Input, 32 CH IPC Alarm Input  
Output 4 CH



An ISO 9001:2008 Certified Company

Triggering

Record, Snap, Preset, Email, etc

### **INTELLIGENT ANALYTICS**

Face

Support Face Detection, Face Recognition, Face Comparison Support Search Image by Image

### **NETWORK**

Interface

RJ45 10/100/1000 Mbps × 1

Network Protocol

IPv4, IPv6, RTSP, UDP, SMTP, NTP, DDNS, DNS, HTTP, HTTPS, FTP, P2P, UPnP, NTP, DHCP, PPPoE, SnMP, ONVIF

Web Client

Multiple user online

### **MOBILE DEVICE**

OS

iOS Andriod

### **STORAGE**

HDD

SATA×4,max 10T per HDD

### **BACK UP**

Local Backup

U Disk,USB Mobile HDD

Network Backup

Yes

### **PORT**

USB

USB 3.0×1,USB 2.0×1 (one in the front panel and other in the Rear panel)

RS485

Yes (full-duplex), connect to PTZ or keyboard

Remote Controller

Yes

### **ELECTRICAL**

Power Supply

ATX

Consumption

≤30W(without HDD)

### **ENVIRONMENTAL**

Work Environment

-10~50 °C, 10%~ 90% humidity

Dimensions(mm)

440×390×70 (W × D × H )



An ISO 9001:2008 Certified Company