

HD-NVR-4108T



Product Features

- ≥ 8 CH Support 6MP/ 5MP / 4MP / 3MP / 1080P / 960P / 720P IP input
- ≥ Adopt standard H.265 and H.264 high profile compression format to get high-quality video at much lower bit rate
- ≥ Intuitive and user-friendly Graphics User Interface (GUI), window style operation by mouse
- ≥ Multi-mode recording: manual / timer / motion
- ≥ Playback : 4 / 8 CH simultaneously playback
- ≥ Search: time slice, time, event (manual, Sensor,Motion), tag search
- ≥ Express and flexible backup via USB, network and so on Pentaplex: preview, record, playback, backup and remote access
- ≥ DHCP, DDNS, PPPoE network protocol,and CMS supported
- ≥ Remote control via IE or CMS : Preview, Playback, backup, PTZ and configuration
- ≥ Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- ≥ Multi-user online simultaneously
- ≥ Authorization management, log review and device status review
- ≥ Support 1080P output, true high resolution display
- ≥ Support PTZ preset and auto cruise, up to 255 presets and 8 cruises
- ≥ Support NAT function and QR Code Scanning by Mobile Phone and PAD
- ≥ Powerful Smart Phone&Pad Surveillance with iOS and Andriod OS



An ISO 9001:2008 Certified Company

Specifications :

SYSTEM

| | |
|-------------|----------------|
| Compression | H.265 Standard |
| OS | Embedded Linux |

VIDEO

| | |
|--------------------|---|
| Incoming Bandwidth | 64Mbps |
| Outgoing Bandwidth | 64Mbps |
| Video Compression | Smart H.265, H.265, H.264 |
| Input Resolution | 6MP, 5MP, 4MP, 3MP, 1080P, 960P, 720P real time |
| Network Access | 8 CH IPC Input |
| Output | HDMI×1:1920×1080/1280×1024/1024×768 VGA×1:1920×1080/1280×1024/1024×768 |

AUDIO

| | |
|-------|----------------------|
| Input | 8 CH IPC Audio Input |
|-------|----------------------|

RECORD

| | |
|---------------|---------------------------------------|
| Resolution | 6MP, 5MP, 4MP, 3MP, 1080P, 960P, 720P |
| Frame Rate | 25fps/30fps (PAL/NTSC) |
| Bit Rate | 32Kbps~8Mbps |
| Image Quality | 5 Level |

PLAYBACK

| | |
|-----------------------|--|
| Simultaneous Playback | Max 8 CH |
| Network Interface | RJ45 10/100Mbps × 1 |
| Network Protocol | IPv4, IPv6, RTSP, UDP, SMTP, NTP, DDNS, DNS, HTTP, HTTPS, FTP, P2P, UPnP, NTP, DHCP, PPPoE, SnMP, ONVIF |

STORAGE

| | |
|-------------------------------|---------|
| HDD | SATA ×1 |
| Max Capacity for 1 single HDD | 8T |



An ISO 9001:2008 Certified Company

BACK UP

USB Backup Yes

INTERFACE

Remote Optional
USB USB 2.0 ×2 (rear panel)

ELECTRICAL

Power Supply DC 12V/1.5 A
Consumption ≤ 5W (without HDD)

ENVIRONMENTAL

Working Environment -10 ~ 50 °C, 10% ~ 90% humidity
Dimension (mm) 255×233×42(W×D×H)
Case Mini 1U



An ISO 9001:2008 Certified Company