

HF-SGFH24-420W



Product Features

- Supports IEEE 802.3af / at standard, automatically detects and identifies devices that comply with the IEEE 802.3af / at standard and supply power to it
- Support Auto MDI/MDIX ;
- Adopt store-and-forward exchange method
- Intelligent power supply, the lowest power consumption, ensure PD power needs
- Provided With power circuit protection, protect the safety of PD
- No configuration characteristics of the power supply is automatically supplied to the adaptive equipment;
- Fanless design, energy saving and environmental protection; no noise, reduce the impact on the environment
- Small, exquisite design
- Support port without link power saving function
- All ports have wire-speed forwarding capability
- Plug and play, easy to use



An ISO 9001:2008 Certified Company

Specifications:

Network standard	IEEE 802.3i, IEEE 802.3u, IEEE 802.3x IEEE 802.3ab, IEEE 802.3af, IEEE 802.3at
Port	24 10/100Mbps RJ45 port 2 10/100/1000Mbps RJ45 Port 1 Gigabit SFP port
PoE	24 10/100/1000Mbps RJ45 port support PoE Max Power 420W Single port max 30W
LEDs	26 Link/Act LEDs 24 POE LEDs 1 Power LEDs
Performance	Forwarding mode: Store-and-Forward Switch Volume (Full-Duplex):8.8Gbps Packet forwarding rate: 6.55Mpps Support 8K MAC address table
Input power	100-240V/50-60Hz
Dimension(L×W×H)	440mm×270mm×44mm



An ISO 9001:2008 Certified Company