

HF-SDH08-120W



Product Features

- ≥ 8x10/100Base-TX Ethernet ports (PoE ports) and 2x10/100BaseTX up-link port
- ≥ Support IEEE802.3af/at standards
- ≥ Max.30W output of single port One-key
- ≥ 6KV surge protection, 8KVESD immunity and anti-interference
- ≥ CCTV Extend:1-4 ports support 250 meters
- ≥ VLAN, AI QoS, AI PoE
- ≥ Built –in Power supply



An ISO 9001:2008 Certified Company

Specifications:

Downlink Ports	8 10/100 Mbps PoE RJ45(Port 1 ~port 8)
Uplink Ports	2 10/100 Mbps RJ45 Port Uplink(Port 9~port 10)
Transfer Rate	100 Mbps full duplex
Network Protocol	IEEE802.3i, IEEE 802.3u, IEEE802.3x, IEEE802.3af, IEEE802.3at
Performance	Bandwidth: 2.0 Gbps(no block) Network Delay(100 to 100Mbps); maximum 20ms(Using 64 byte packet) Frame filtering and transmission rate Forward rate: 1.48Mpps
LED Indicator	Power, Link/ACT, RESV, PoE Indicator Light
Data Transfer	Shall support Auto detection of Full duplex / Half Duplex on all ports
Media	Shall support Auto MDI/ MDIX on all ports IEEE 802.3, 802.3u, 802.3x
MAC address table	8K MAC address entries
PoE Pin	1/2+, 3/6- Power
Max power for single port	30w Internal Power Supply: 96W
Dimensions	210mm x 40mm x 152mm
Weight	1.5 kg
Operating Temperature	0° ~ 40° C
Operating Humidity	10% ~ 90%, Non-Condensing



An ISO 9001:2008 Certified Company