

HD-XVR-5322H2-H



Product Features

- Embedded processor
- H.265+/H.265 dual- stream video compression
- Support HDCVI/AHD/TVI/CVBS/IP video inputs
- Max 32channels IP camera inputs, each channel up to 6MP
- Max 128Mbps incoming bandwidth
- Long transmission distance over coax cable
- Smart Search and Intelligent Video System



An ISO 9001:2008 Certified Company

Specifications:

SYSTEM

Main Processor	Embedded Processor
Operating System	Embedded LINUX

VIDEO AND AUDIO

Analog Camera Input	32Channel, BNC
HDCVI Camera	5MP, 4MP, 1080P@25/30fps, 720P@50/60fps, 720P@25/30fps
AHD Camera	5MP, 4MP, 1080P@25/30, 720P@25/30fps
TVI Camera	5MP, 4MP, 1080P@25/30, 720P@25/30fps
CVBS Camera	PAL/NTSC
IP Camera Input	32, each channel up to 6MP
Audio In/Out	1/1, RCA
Two-way Talk	Reuse audio in/out, RCA

RECORDING

Video Compression	H.265+/H.265/H.264+/H.264
Resolution	5M-N, 4M-N, 1080P,1080N, 720P, 960H, D1, CIF
Record Rate	Main Stream: the 1st channel& 2nd channels 5M-N(1~10fps); other channels 4M-N/1080P(1~15fps); 1080N/720P/960H/ D1/CIF (1~25/30fps) Sub stream: 4CH: CIF/QCIF (1~15fps)
Video Bit Rate	32Kbps ~ 4096Kbps Per Channel
Record Mode	Manual, Schedule (General, Continuous), MD (Video detection: Motion Detection, Video Loss, Tampering), Alarm, Stop
Record Interval	1 ~ 60 min (default: 60 min), Pre-record: 1 ~ 30 sec, Postrecord: 10 ~ 300 sec
Audio Compression	AAC(only for the 1st channel), G.711A, G.711U, PCM
Audio Sample Rate	8KHz, 16 bit Per Channel
Audio Bit Rate	64Kbps Per Channel



An ISO 9001:2008 Certified Company

DISPLAY

Interface	1 HDMI ,1 VGA, 1 TV
Resolution	HDMI:3840×2160, 2560×1440, 1920×1080, 1280×1024, 1280×720 VGA: 1920×1080, 1280×1024, 1280×720
Multi-screen Display	1/4/6/8/9/16/25/36
OSD	Camera title, Time, Video loss, Camera lock, Motion detection, Recording

NETWORK

Interface	1 RJ-45 Port (1000M)
Network Function	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, RTSP, UDP, SMTP, NTP, DHCP, DNS, IP Filter ,DDNS, FTP, Alarm Server, P2P,IP Search(Supports IP camera, NVR, etc.)
Max. User Access	128 users
Smart Phone	iPhone, iPad, Android
Interoperability	ONVIF

VIDEO DETECTION AND ALARM

Trigger Events	Recording, PTZ, Tour, Video Push, Email, FTP, Snapshot, Buzzer and Screen Tips
Video Detection	Motion Detection, MD Zones: 396 (22 × 18), Video Loss, Tampering and Diagnosis

PLAYBACK AND BACKUP

Playback	1/4/9/16
Search Mode	Time /Date, Alarm, MD and Exact Search (accurate to second)
Playback Function	Play, Pause, Stop, Rewind, Fast play, Slow Play, Next File,
Previous	File, Next Camera, Previous Camera, Full Screen, Repeat, Shuffle, Backup Selection, Digital Zoom
Backup Mode	USB Device/Network



STORAGE

Internal HDD 2 SATA Port, up to 10TB capacity

AUXILIARY INTERFACE

USB 1 USB 2.0, 1 USB 3.0
RS485 1 Port, for PTZ Control

ELECTRICAL

Power Supply DC12V/5A
Power Consumption <10W (Without HDD)

ENVIRONMENTAL

Operating Conditions -10°C ~ +55°C (+14°F ~ +131°F), 0~ 90% RH
Storage Conditions -20°C ~ +70°C (-4°F ~ +158°F) , 0~ 90% RH

CONSTRUCTION

Dimensions Compact 1U, 375×287×53mm
(14.8"×11.3"×2.1")
Net Weight 2.0kg (4.4lb) (without HDD)
Gross Weight 3.3kg (7.3lb)
Installation Desktop installation



An ISO 9001:2008 Certified Company