

## HD-XVR-4116THL



### Product Features

- 16 CH Support TVI / CVI / AHD Video Input,1080P lite / 720P / 720P lite / WD1 recording
- 16 CH Support 2 CH IPC 3MP / 1080P / 960P / 720P recording
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphics User Interface ( GUI ), window style operation by Mouse
- Multi-mode recording: Manual / Timer / Motion
- Playback : Simultaneously playback, Multi-user online simultaneously
- Search: time slice, time, event ( manual, motion ), tag search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol, IE browse and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network Transmission and remote surveillance with mobile device
- Authorization management, log review and device status review
- HDMI 1080P output,true high resolution display
- Support PTZ Preset and auto cruise, up to 255 Presets and 8 cruises
- Support NAT function and QR Code scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with IOS and Andriod OS



An ISO 9001:2008 Certified Company

## Specifications :

### SYSTEM

Main Processing Chip	Cortex A9
OS	Embedded Linux

### VIDEO

Network Access Bandwidth	12 Mbps
Compression	H.265 Standard
Input Resolution	TVI/CVI/AHD: 1080P Lite, 720P, WD1 real time
Local Video Input	BNC×16
Network Input Bandwidth	IPC×2
Output	HDMI×1:1920×1080/1280×1024/1024×768 VGA×1:1920×1080/1280×1024/1024×768

### AUDIO

Local Audio Input	RCA ×1
2-way Audio	Take up Channel One Audio Input
Local Output	RCA ×1

### RECORD

Resolution	1080P lite, 720P, 720P lite, WD1
Bite Stream	786Kbps-4Mbps
Image Quality	5 Level
Local Record Frame rate	1080P lite/720P: 12fps (PAL)/ 15fps (NTSC) 720P lite/WD1: 25fps (PAL)/30fps ( NTSC)
Mode	Manual, Timer, Motion

### IPC INPUT

Resolution	3MP/1080P/960P/720P
IPC Record Frame Rate	25fps (PAL)/30fps (NTSC)



An ISO 9001:2008 Certified Company

### **PLAYBACK**

Simultaneous Playback

Max 16 CH

### **NETWORK**

Interface

RJ45 10/100Mbps × 1

Network Protocol

TCP/IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP  
SMTP, ONVIF

### **STORAGE**

HDD

SATA×1

Max Capacity for 1 Single HDD

8T

### **BACK UP**

USB Backup

Yes

### **INTERFACE**

Remote

Optional

USB

USB2.0×2(in the rear panel)

### **ENVIRONMENTAL**

Power Supply

DC12V

Power Consumption

≤ 10W (without HDD)

Working Environment

-10~50 °C, 10%~90% humidity

### **CONSTRUCTION**

Dimension

255×223×42(W×D×H)

Computer Case

mini 1U



An ISO 9001:2008 Certified Company