

## HD-XVR-5116TL



### Product Features

- 16 CH Support TVI / CVI / AHD Video Input, Support 5MP Lite /4MP Lite/1080P/720P/WD1
- 16 CH Support CVI video input, support 4MP Lite /1080P/ 720P/WD1
- 16 CH DVR Support Default 4 / 8 CH IPC 4MP / 3MP / 1080P / 960P / 720P recording
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphics User Interface ( GUI ), window style operation by mouse
- Multi-mode recording: manual / timer / motion
- Playback : 16 CH simultaneously playback
- Search: time slice, time, event ( manual, motion ), tag search
- Express and flexible backup via USB, network and so on Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol, IE browse and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network transmission and remote surveillance with mobile device
- Multi-user online simultaneously
- Authorization management, log review and device status review
- Support 1080P output, true high resolution display
- Support PTZ preset and auto cruise, up to 255 presets and 8 cruises



An ISO 9001:2008 Certified Company

## Specifications :

### SYSTEM

Main Processing Chip	Cortex A9
OS	Embedded Linux

### VIDEO

Network Access Bandwidth I/O	72/80 Mbps
Compression	H.265 Standard High Profile
Input	BNC × 16
Resolution	TVI/AHD : 5MP/4MP/1080P/720P/WD1 CVI : 4MP/1080P/720P/WD1
IP Input	8 CH (Up to 16CH)
Output	HDMI × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768 VGA × 1 : 1920 × 1080 / 1280 × 1024 / 1024 × 768 BNC × 1 : CVBS ( used as the main or spot output )

### AUDIO

Input	RCA × 1
Output	RCA × 1
Two-way audio	Take up channel one audio input

### RECORD

Resolution	5MP Lite/4MP Lite/1080P/1080P Lite/720P/WD1
Frame Rate	5MP Lite :10fps 4MP Lite : 12fps (PAL)/15fps (NTSC) 1080P : 12fps (PAL)/15fps (NTSC) 1080P Lite/720P/WD1 : 25fps (PAL)/30fps (NTSC)
Bit Rate	32Kbps ~ 5Mbps
Mode	Manual, Timer, Motion

### IPC INPUT

Resolution	Up to 5MP@25fps
------------	-----------------



### **PLAYBACK**

Playback  
Search  
Smart Search

16 CH  
Time Slice/Time/Event/Tag Search  
Highlight colors to display the camera record in a certain period of time, different colors refer to different record events  
Play, Pause, FF, FB, Digital Zoom etc

### **ALARM**

Mode

Manual, Motion, Exception

### **NETWORK**

Interface  
Protocol

RJ45 100Mbps × 1  
TCP / IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP, SMTP, ONVIF

### **MOBILE DEVICES**

OS

iOS, Android

### **STORAGE**

HDD  
Max Capacity for 1 Single HDD

SATA × 1  
8T

### **BACK UP**

Local Backup  
Network Backup

U Disk, USB removable HDD  
Yes

### **PORT**

RS485  
USB  
Remote Controller

RS485 × 1, connect to PTZ or keyboard  
USB 2.0 × 2 ( in the rear panel )  
Optional

### **CONSTRUCTION**

Power Supply  
Consumption  
Working Environment  
Dimensions

DC12V / 3A  
≤ 5W ( without HDD )  
-10 ~ 50 °C, 10% ~ 90% humidity  
255 × 233 × 42 ( W × D × H )



An ISO 9001:2008 Certified Company