

HD-XVR-4232TH



Product Features

- 32 CH Support TVI / CVI / AHD Video Input, 1080P/1080P lite/720P/ WD1 recording
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and User-Friendly Graphics User Interface (GUI), Window Style Operation by Mouse
- Multi-mode recording: manual / timer / motion
- Playback : Support 16CH Simultaneously Playback
- Multi-user online simultaneously
- Search: time slice, time, event (manual, motion), tag search
- Express and flexible backup via USB, Network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol, IE browse and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network Transmission and remote surveillance with mobile device
- Authorization management, log review and device status review
- HDMI 1080P output,true high resolution display
- Support PTZ Preset and auto cruise, up to 255 Presets and 8 cruises
- Support NAT function and QR Code scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with IOS and Andriod OS



An ISO 9001:2008 Certified Company

IPC INPUT

Resolution 3MP/1080P/960P/720P
IPC Record Frame Rate 25fps (PAL)/30fps (NTSC)

PLAYBACK

Simultaneous Playback Max 16 CH

NETWORK

Interface RJ45 10/100 Mbps × 1
Network Protocol TCP/IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP
SMTP, ONVIF

STORAGE

HDD SATA×2
Max Capacity for 1 Single HDD 8T

BACK UP

USB Backup Yes

INTERFACE

Alarm Input 4
Alarm Output 1
Communication RS485×1, connect to PTZ or keyboard
Remote Optional
USB USB2.0×1(front panel), USB3.0×1 (rear panel)

ENVIRONMENTAL

Power Supply ATX
Power Consumption ≤40W (without HDD)
Working Environment -10~50 °C, 10%~90% humidity

CONSTRUCTION

Dimension 440×390×70(W×D×H)
Computer Case 1.5U



An ISO 9001:2008 Certified Company