

## HD-XVR-5432THC



### Product Features

- 32 CH Support TVI / CVI / AHD 5MP/4MP/1080P/720P/WD1 video input
- 32 CH Support 8CH 5MP/4MP/3MP/1080P/960P/720P IP video input
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphics User Interface (GUI), window style operation by Mouse
- Multi-type recording: manual / schedule / sensor / motion /analytics recording Playback : 16 CH simultaneously playback
- Search: time slice, time, event, tag and smart search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web Client or CMS : preview, playback, backup, PTZ and configuration
- Multi-user online simultaneously
- Authorization management, log review and device status review, HDMI 1080P output, true high resolution display, Support PTZ Preset and auto cruise, up to 255 Presets and 8 cruises
- Support NAT function and QR Code scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with IOS and Andriod OS



An ISO 9001:2008 Certified Company

## Specifications :

### SYSTEM

OS Embedded Linux

### VIDEO

Incoming Bandwidth 40Mbps  
 Outgoing Bandwidth 160Mbps  
 Video Compression H.264/H.265  
 IP Video Input 8CH (upto 24CH) , Up to 5MP@30fps  
 Analog Video Input BNC × 32  
 BNC interface (1.0Vp-p; 75Ω)  
 Input Resolution TVI/AHD/CVI: 5MP@20fps;  
 4MP/3MP/1080P/720P/WD1@25fps/30fps (live)  
 Output HDMI×1: 1920×1080/1280×1024/1024×768  
 VGA×1: 1920×1080/1280×1024/1024×768  
 BNC×1: CVBS (used as the main or spot output)  
 Multi-screen Display 1/4/6/8/9/13/16/25/32/36

### AUDIO

Local Audio Input RCA ×16  
 2-way Audio Take up Channel One Audio Input  
 Local Output RCA × 1 (linear, 600Ω)  
 Compression G.711(U/A)

### RECORD

Resolution 5MP Lite/4MP Lite / 1080P/1080P Lite/720P/WD1/D1  
 Local Record Frame Rate 5MP Lite :10fps; 4MP Lite/1080P : 12fps (PAL)/15fps (NTSC);  
 1080P Lite/720P/WD1/D1@25fps (PAL)/30fps (NTSC)  
 Bite Stream 32Kbps - 5Mbps

### PLAYBACK

Simultaneous Playback 16 CH  
 Search Time slice / time / event / tag search  
 Smart Search Highlight colors to display the camera record in a certain period  
 of time, different colors refer to different record events  
 Function Play, pause, FF, FB, digital zoom, etc



An ISO 9001:2008 Certified Company

### **ALARM**

Mode Manual, motion, exception, smart event

### **NETWORK**

Interface RJ45 10/1000Mbps × 1  
Network Protocol TCP/IP, PPPoE, DHCP, DNS, DDNS, UPnP, HTTP, HTTPS, NTP, SMTP  
Client Connection Max. 10 users access

### **MOBILE DEVICE**

OS iOS, Android

### **STORAGE**

HDD SATA×4, up to 10TB per HDD; E-SATA×1

### **BACK UP**

Local Backup U disk, USB mobile HDD  
Network Backup Yes

### **PORT**

RS 485 Yes (full-duplex), connect to PTZ or keyboard  
USB USB 2.0 × 1; USB 3.0 × 1  
Remote Controller Optional

### **ENVIRONMENTAL**

Power Supply ATX-250W  
Power Consumption ≤ 30W (without HDD)  
Working Environment -10 ~ 50 °C, 10%~90% humidity



An ISO 9001:2008 Certified Company