

HD-XVR-4104TH



Product Features

- 4 CH Support TVI / CVI / AHD Video Input, 1080P lite / 720P / WD1 recording
- 4 CH Support 1 / 1 CH IPC 1080P / 960P / 720P recording
- Adopt standard H.265 High Profile Compression Format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphics User Interface (GUI), window style operation by mouse, Multi-mode recording: manual / timer / motion
- Playback : Simultaneously playback, Multi-user online simultaneously
- Search: time slice, time, event (manual, motion), tag search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol, IE browser and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network Transmission and remote surveillance with mobile device
- Authorization management, log review and device status review, HDMI 1080P output, true high resolution display, Support PTZ Preset and auto cruise, up to 255 Presets and 8 cruises
- Support NAT function and QR Code scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with IOS and Andriod OS



An ISO 9001:2008 Certified Company

Specifications :

SYSTEM

Main Processing Chip	Cortex A7
OS	Embedded Linux

VIDEO

Incoming Bandwidth	6Mbps
Video Compression	H.265 standard
Network Input	IPC×1
Input Resolution	TVI/CVI/AHD: 1080P Lite, 720P, WD1 real time
Local Video Input	BNC×4
Output	HDMI×1:1920×1080/1280×1024/1024×768 VGA×1:1920×1080/1280×1024/1024×768

AUDIO

Local Audio Input	RCA ×1
2-way Audio	Take up Channel One Audio Input
Local Output	RCA ×1

RECORD

Resolution	1080P lite, 720P, WD1
Local Record Frame Rate	1080P lite/720P/WD1:25fps (PAL)/30fps (NTSC)
Mode	Manual, Motion, Exception, Smart event
Bite Stream	786Kbps-4Mbps
Image Quality	5 Level

IPC INPUT

Resolution	1080P/960P/720P
IPC Record Frame Rate	25fps (PAL)/30fps(NTSC)
IPC Record Frame Rate	25fps(PAL)/30fps(NTSC)



An ISO 9001:2008 Certified Company

PLAYBACK

Simultaneous Playback

Max 4 CH

NETWORK

Interface

RJ45 10/100Mbps × 1

Network Protocol

TCP/IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP,
SMTP, ONVIF**STORAGE**

HDD

SATA×1

Max Capacity for 1 Single HDD

8T

BACK UP

USB Backup

Yes

INTERFACE

Remote

Optional

USB

USB2.0×2(in the rear panel)

ENVIRONMENTAL

Power Supply

DC12V/1.5A

Power Consumption

≤ 5W (without HDD)

Working Environment

-10~50 °C, 10%~90% humidity

CONSTRUCTION

Dimension

255×223×42(W×D×H)

Computer Case

mini 1U



An ISO 9001:2008 Certified Company