

HD-XVR-4104THC



Product Features

- 4 CH Support TVI / CVI / AHD 1080/1080P lite/720P/WD1 video input
- 4 CH Support 2 CH 1080P / 960P / 720P video input
- 4CH DVR: 4CH analog video input can be switched to 4CH IP video input
- Adopt standard H.265 High Profile Compression Format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphics User Interface (GUI), window style operation by mouse,Multi-mode recording: manual / timer / motion
- Playback : 4 CH imultaneously playback
- Search: time slice, time, event, tag search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol, IE browser and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network Transmission and remote surveillance with mobile device
- Authorization management, log review and device status review,HDMI 1080P output, true high resolution display,Support PTZ Preset and auto cruise, up to 255 Presets and 8 cruises
- Support NAT function and QR Code scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with IOS and Andriod OS



An ISO 9001:2008 Certified Company

Specifications :

SYSTEM

OS Embedded Linux

VIDEO

Incoming Bandwidth 10Mbps
 Outgoing Bandwidth 30Mbps
 Video Compression H.264/H.265
 IP Video Input 2CH (upto 6CH); Up to 2MP@30fps
 Analog Video Input BNCx4
 BNC interface (1.0Vp-p; 75Ω)
 Input Resolution TVI/AHD/CVI:1080P/1080P Lite/720P/720P Lite/WD1
 Output HDMI×1:1920×1080/1280×1024/1024×768
 VGA×1:1920×1080/1280×1024/1024×768
 Multi-screen Display 1/4/6/9

AUDIO

Local Audio Input RCA ×1
 2-way Audio Take up Channel One Audio Input
 Local Output RCA × 1 (linear, 600Ω)
 Compression G.711(U/A)

RECORD

Resolution 1080P Lite/720P/720P Lite/WD1
 Local Record Frame Rate 1080P lite/720P/WD1:25fps (PAL)/30fps (NTSC)
 Bite Stream 32Kbps - 4Mbps

PLAYBACK

Simultaneous Playback 4 CH
 Search Time slice / time / event / tag search
 Smart Search Highlight colors to display the camera record in a certain period of time, different colors refer to different record events
 Function Play, pause, FF, FB, digital zoom, etc



An ISO 9001:2008 Certified Company

ALARM

Mode Manual, motion, exception, smart event

NETWORK

Interface RJ45 10/100Mbps × 1
Network Protocol TCP/IP, PPPoE, DHCP, DNS, DDNS, UPnP, HTTP, HTTPs, NTP, SMTP
Client Connection Max. 5 users access

MOBILE DEVICE

OS iOS, Andriod

STORAGE

HDD SATA×1, upto 8TB

BACK UP

Local Backup U disk, USB mobile HDD
Network Backup Yes

PORT

USB USB2.0×2

ENVIRONMENTAL

Power Supply DC12V/1.5A
Power Consumption ≤ 5W (without HDD)
Working Environment -10 ~ 50 °C, 10%~90% humidity
Dimensions(mm) 255 × 222 × 42 (W × D × H)



An ISO 9001:2008 Certified Company