

## HD-XVR-4104TLC



### Product Features

- 4 CH Support TVI / CVI / AHD 1080P/ 1080P Lite/ 720P/ 720P Lite/WD1 video input
- 4 CH Support 2 CH IP video input by default,
- 4 CH analog video input can be switched to 4 CH IP video input
- Adopt standard H.265 High Profile Compression Format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphics User Interface ( GUI ), window style operation by mouse,Multi-mode recording: manual / timer / motion
- Playback : 4 CH imultaneously playback
- Search: time slice, time, event, tag search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol, IE browser and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network Transmission and remote surveillance with mobile device
- Authorization management, log review and device status review,HDMI 1080P output, true high resolution display, Support PTZ Preset and auto cruise, up to 255 Presets and 8 cruises
- Support NAT function and QR Code scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with IOS and Andriod OS



## Specifications :

### SYSTEM

OS Embedded Linux

### VIDEO

Incoming Bandwidth 10Mbps  
 Outgoing Bandwidth 30Mbps  
 Video Compression H.264/H.265  
 IP Video Input 2CH, Up to 2MP@30fps  
 Analog Video Input BNC×4  
 BNC interface (1.0Vp-p; 75Ω)  
 Input Resolution TVI/AHD/CVI: 1080P/1080P Lite/720P/720P Lite/WD1  
 Output HDMI×1:1920×1080/1280×1024/1024×768  
 VGA×1:1920×1080/1280×1024/1024×768  
 Multi-screen Display 1/4/6/9

### AUDIO

Local Audio Input RCA ×1  
 2-way Audio Take up Channel One Audio Input  
 Local Output RCA × 1 (linear, 600Ω)  
 Compression G.711(U/A)

### RECORD

Resolution 1080P Lite/720P/WD1  
 Frame Rate Analog Channel: 1080P Lite/720P/WD1: 25fps (PAL)/30fps (NTSC)  
 IP Channel: 25fps(PAL) / 30fps (NTSC)  
 Bit Rate 32Kbps - 4Mbps

### PLAYBACK

Simultaneous Playback 4 CH  
 Search Time slice / time / event / tag search  
 Smart Search Highlight colors to display the camera record in a certain period  
 of time, different colors refer to different record events  
 Function Play, pause, FF, FB, digital zoom, etc



**ALARM**

Mode Manual, motion, exception, smart event

**NETWORK**

Interface RJ45 10/100Mbps × 1  
Network Protocol TCP/IP, HTTP, HTTPS, 802.1x, FTP, DHCP, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IPv6, UDP, WebSocket, PPPoE, SNMP, IGMP  
Client Connection Max. 5 users access

**MOBILE DEVICE**

OS iOS, Android

**STORAGE**

HDD SATA×1, upto 8TB

**BACK UP**

Local Backup U disk, USB mobile HDD  
Network Backup Yes

**PORT**

USB USB2.0×2 (in the rear panel)

**ENVIRONMENTAL**

Power Supply DC12V/1.5A  
Power Consumption ≤ 5W (without HDD)  
Working Environment -10 ~ 50 °C, 10%~90% humidity



An ISO 9001:2008 Certified Company