

HD-XVR-4108TH



Product Features

- 8 CH Support TVI / CVI / AHD Video Input,1080P lite / 720P / 720P lite / WD1 recording
- 8 CH Support 1 / 1 CH IPC 1080P / 960P / 720P recording
- Adopt standard H.265 high profile compression format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphics User Interface (GUI), window style operation by Mouse
- Multi-mode recording: manual / timer / motion
- Playback : Simultaneously playback, Multi-user online simultaneously
- Search: time slice, time, event (manual, motion), tag search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol, IE browse and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network Transmission and remote surveillance with mobile device
- Authorization management, log review and device status review
- HDMI 1080P output,true high resolution display
- Support PTZ Preset and auto cruise, up to 255 Presets and 8 cruises
- Support NAT function and QR Code scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with IOS and Andriod OS



An ISO 9001:2008 Certified Company

Specifications :

SYSTEM

Main Processing Chip	Cortex A7
OS	Embedded Linux

VIDEO

Network Access Bandwidth	6 Mbps
Video Compression	H.265 Standard
Network Input	IPC×1
Input Resolution	TVI/CVI/AHD: 1080P Lite,720P, WD1 real time
Local Video Input	BNC×8
Output	HDMI×1:1920×1080/1280×1024/1024×768 VGA×1:1920×1080/1280×1024/1024×768

AUDIO

Local Audio Input	RCA ×1
2-way Audio	Take up Channel One Audio Input
Local Output	RCA ×1

RECORD

Resolution	1080P lite, 720P, 720P lite, WD1
Bite Stream	786Kbps-4Mbps
Image Quality	5 Level
Local Record Frame Rate	1080P lite/720P:12fps(PAL)/15fps (NTSC) 720P lite/WD1:25fps(PAL)/30fps(NTSC)
Mode	Manual,Timer,Motion

IPC INPUT

Resolution	1080P/960P/720P
IPC Record Frame Rate	25fps (PAL)/30fps(NTSC)

PLAY BACK

Simultaneous Playback	Max 8 CH
-----------------------	----------



NETWORK

Interface	RJ45 10/100Mbps × 1
Network Protocol	TCP/IP, PPPoE, DHCP, DNS, DDNS, UPnP, NTP SMTP, ONVIF

STORAGE

HDD	SATA×1
Max Capacity for 1 Single HDD	8T

BACK UP

USB Backup	Yes
------------	-----

INTERFACE

Remote	Optional
USB	USB2.0×2(in the rear panel)

ENVIRONMENTAL

Power Supply	DC12V
Power Consumption	≤ 5W (without HDD)
Working Environment	-10~50 °C, 10%~90% humidity

CONSTRUCTION

Dimension	255×223×42(W×D×H)
Computer Case	mini 1U



An ISO 9001:2008 Certified Company