

HD-XVR-4108TLC



Product Features

- 8 CH Support TVI / CVI / AHD 1080P/ 1080P Lite/ 720P/ 720P Lite/WD1 video input
- 8 CH Support 2 CH IP video input by default,
- 8 CH analog video input can be switched to 8 CH IP video input
- Adopt standard H.265 High Profile Compression Format to get high-quality video at much lower bit rate
- Intuitive and user-friendly Graphics User Interface (GUI), window style operation by mouse,Multi-mode recording: manual / timer / motion
- Playback : 8 CH imultaneously playback
- Search: time slice, time, event, tag search
- Express and flexible backup via USB, network and so on
- Pentaplex: preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol, IE browser and CMS supported
- Remote control via IE or CMS : preview, playback, backup, PTZ and configuration
- Dual stream technology for local storage with high definition, remote network Transmission and remote surveillance with mobile device
- Authorization management, log review and device status review,HDMI 1080P output, true high resolution display, Support PTZ Preset and auto cruise, up to 255 Presets and 8 cruises
- Support NAT function and QR Code scanning by mobile phone and PAD
- Powerful smart phone & Pad surveillance with IOS and Andriod OS



Specifications :

SYSTEM

OS Embedded Linux

VIDEO

Incoming Bandwidth 16Mbps
 Outgoing Bandwidth 60Mbps
 Video Compression H.264/H.265
 IP Video Input 2CH, Up to 5MP@25fps
 Analog Video Input BNC×8
 BNC interface (1.0Vp-p; 75Ω)
 Input Resolution TVI/AHD/CVI: 1080P/1080P Lite/720P/720P Lite/WD1
 Output HDMI×1:1920×1080/1280×1024/1024×768
 VGA×1:1920×1080/1280×1024/1024×768
 Multi-screen Display 1/4/6/8/9/13/16

AUDIO

Local Audio Input RCA ×1
 2-way Audio Take up Channel One Audio Input
 Local Output RCA × 1 (linear, 600Ω)
 Compression G.711(U/A)

RECORD

Resolution 1080P Lite/720P/720P Lite/WD1
 Frame Rate Analog channel: 1080P Lite/720P/WD1: 25fps (PAL)/30fps (NTSC)
 (only CH 1 supports) 1080P Lite/720P/WD1: 12fps (PAL)/15fps (NTSC) (other channels support) 720PLite: 25fps(PAL) / 30fps(NTSC)
 IP Channel: 25fps(PAL) / 30fps (NTSC)
 Bit Rate 32Kbps - 4Mbps

PLAYBACK

Simultaneous Playback 8 CH
 Search Time slice / time / event / tag search
 Smart Search Highlight colors to display the camera record in a certain period of time, different colors refer to different record events



ALARM

Mode Manual, motion, exception, smart event

NETWORK

Interface RJ45 10/100Mbps × 1
Network Protocol TCP/IP, HTTP, HTTPS, 802.1x, FTP, DHCP, DDNS, RTP, RTSP, RTCP, NTP, UPnP, SMTP, IPv6, UDP, WebSocket, PPPoE, SNMP, IGMP
Client Connection Max. 5 users access

MOBILE DEVICE

OS iOS, Android

STORAGE

HDD SATA×1, upto 8TB

BACK UP

Local Backup U disk, USB mobile HDD
Network Backup Yes

PORT

USB USB2.0×2 (in the rear panel)

ENVIRONMENTAL

Power Supply DC12V/1.5A
Power Consumption ≤ 5W (without HDD)
Working Environment -10 ~ 50 °C, 10%~90% humidity

