

HF-SI04-60W



Product Features

- Using CAT.5 network patch cords support power for the wireless AP and IP camera/PTZ camera/PTZ
- Networking standard: IEEE802.3af/at/bt
- PoE Watchdog AI Function: Detection front-end PoE cameras and PD, Automatic detection, Automatic restart
- Support 60W PoE receiving power, free of power adapter & simplify power supply
- 6KV lightning protection, 8KV surge protection, anti-reverse connection, over-current protection, over-voltageprotection,over-temperature protection, Short circuit protection
- The Max output power of the port is 60W, which is convenient for hi-power equipment
- Zero configuration feature power supply is automatically supplied to the adaptive equipment



Specifications:

Ports	4 x 10/100/100Mbps PoE ports (RJ45) 2 x 10/100Mbps uplink port (RJ45)
Transmission Rate	200Mbps Full Duplex; 10 or 100 Mbps Half Duplex
Transmission Distance	100Mbps /10Mbps Adaptive MAX 250m
Performance Specification	Bandwidth: 1.2Gbps Network Latency (10 to 1000Mbps): $\leq 16\mu s$ (use the 64byte package size) MAC address table: 2K The Frame Filter & Transmission Rate: 14800pps the most for 10M port, 148800pps the most for 100M port
Networking Standard	IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3xFlowControl IEEE 802.3af/at/bt Power over Ethernet
Power Support	Power input: AC 110~220V Total $\leq 65W$ PoE Watchdog: Port 1~4 Power output: PoE1~3Port:1/2(+52V),3/6(GND) $\leq 30W$ PoE 4 Port:1245(+53V),3678(GND) compatible1/2(+52V),3/6(GND) $\leq 60W$
Protection Level	Lightning Protection: 6KV ESD Protection: 8KV
Physical Specifications	Size(L*W*H) : 187mm*139mm*43mm
Working Environment	Operating Temperature: -30°C ~60°C Storage Temperature: -40°C ~70°C Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing

