

## HC-FS20N2

## **Product Features**

- > Wide view angle, cover more and see more
- 3MP Full HD to see the smallest details even in night vision
- Support Upto 128GB SD card , local storage to protect privacy
- Moon detecon and intelligent alerts
- <sup>></sup> 2-way Audio to listen and talk back
- Protocol ODM: HTTPAPI SDK, RTSP, RTMP, HLS, FTP, SFTP, NAS
- Very low Bandwidth required, run smoothly in 8KB web
- ONVIF Complaints



## **VIDEO COMPRESSION**

Compression Code Rate Core Chipset Resolution Frame Rates Min Illumination IR Distance CMOS Feature Zoom Lens/Viewing Angle SYSTEM FEATURE

Mobile phone monitor Plug and Play

Security

H.264 HP 16-4096 Kbps Hi3518Ev200 Chipset 3MP 30fps Color: 0.05Lux; W/B: 0Lux with IR LED on IR cut filter auto switch on, IR 10 meters Support AWB, AGC, BLC 10x Digital Zoom 20°~180°

Both workable for iOS and Android P2P technology, network penetration up to 99% Adapt to all kinds of complex network. Administation for account and password

An ISO 9001:2008 Certified Company



\* Design and specifications are subject to change without notice



Audio Input		38dB microphone
Audio Output		Built in speaker (8Ω1W)
RECORDING MAN	AGEMENT	
Recording Mode		Manual recording, timing recording and alarm recording
Video Storage		TF card (support 8G - 128G)
Protocols		TCP/IP,HTTP,TCP,UDP,SMTP,DHCP,DNS,DDNS,NTP UPnP,P2P,etc
Wi-Fi		Wi-Fi802.11b/g/n 2.4G wireless network
Alarm Action		Capture Photo, send emails, APP notification
SYSTEM REQUIRE	MENT	
System Configurat	ion	Android 4.0 and above; iOS 8.0 and above
Material		Engineering plastics
Working Environm	ient	Indoor
Power Supply		DC5V 2A
Working Temperat	ture	-10 <sup>°</sup> c~+50 °c
GENERAL		
Working Humidity	9	95% RH
Dimensions	(	65mm*65mm*165mm(Length*Width*Height)

65mm\*65mm\*165mm(Length\*Width\*Height) <300g



An ISO 9001:2008 Certified Company



Weight

\* Design and specifications are subject to change without notice